



Water Environment Research Foundation
Collaboration. Innovation. Results.

Wastewater Treatment and Reuse



**FINAL
REPORT**

Small-Scale Constructed
Wetland Treatment Systems
Feasibility, Design Criteria, and O&M Requirements



01-CTS-5

**SMALL-SCALE CONSTRUCTED
WETLAND TREATMENT SYSTEMS**
FEASIBILITY, DESIGN CRITERIA, AND O&M REQUIREMENTS

by:

Scott D. Wallace, P.E.
North American Wetland Engineering, LLC

Robert L. Knight, Ph.D.
Wetland Solutions, Inc.

2006



The Water Environment Research Foundation, a not-for-profit organization, funds and manages water quality research for its subscribers through a diverse public-private partnership between municipal utilities, corporations, academia, industry, and the federal government. WERF subscribers include municipal and regional water and wastewater utilities, industrial corporations, environmental engineering firms, and others that share a commitment to cost-effective water quality solutions. WERF is dedicated to advancing science and technology addressing water quality issues as they impact water resources, the atmosphere, the lands, and quality of life.

For more information, contact:
Water Environment Research Foundation
635 Slaters Lane, Suite 300
Alexandria, VA 22314-1177
Tel: (703) 684-2470
Fax: (703) 299-0742
www.werf.org
werf@werf.org

This report was co-published by the following organizations. For nonsubscriber sales information, contact:

IWA Publishing
Alliance House, 12 Caxton Street
London SW1H 0QS, United Kingdom
Tel: +44 (0) 20 7654 5500
Fax: +44 (0) 20 7654 5555
www.iwapublishing.com
publications@iwap.co.uk

© Copyright 2006 by the Water Environment Research Foundation. All rights reserved. Permission to copy must be obtained from the Water Environment Research Foundation.
Library of Congress Catalog Card Number: 2004109532
Printed in the United States of America
IWAP ISBN: 1-84339-728-5

This report was prepared by the organization(s) named below as an account of work sponsored by the Water Environment Research Foundation (WERF). Neither WERF, members of WERF, the organization(s) named below, nor any person acting on their behalf: (a) makes any warranty, express or implied, with respect to the use of any information, apparatus, method, or process disclosed in this report or that such use may not infringe on privately owned rights; or (b) assumes any liabilities with respect to the use of, or for damages resulting from the use of, any information, apparatus, method, or process disclosed in this report.

North American Wetland Engineering, LLC, Knapp Design

This document was reviewed by a panel of independent experts selected by WERF. Mention of trade names or commercial products does not constitute WERF endorsement or recommendations for use. Similarly, omission of products or trade names indicates nothing concerning WERF's positions regarding product effectiveness or applicability.

ACKNOWLEDGMENTS

The project team would like to acknowledge and thank the numerous individuals who generously provided information for this project, including, but not limited to: Bill Grant (*Lagrange County, Indiana*); Dave Flowers P.E.; Margaret Medellin (*Denver Water, Colorado*); David Steer (*University of Akron, Ohio*); Richard Weaver (*Texas A&M University*); Paul Cooper (*WRc, United Kingdom*); Fabio Masi (*IRIDRA, Italy*); Gabrielle Mitterer-Reichmann (*OEPRO, Austria*); Chris Tanner (*NIWA, New Zealand*); Frank van Dien (*Ecofyf, The Netherlands*); Dion van Oirschot (*Rietland, The Netherlands*); Adrian Hanson (*New Mexico State University*); John Pries (*CH2M Hill Canada*); Catherine Boutin (*Cemagref, France*); and Frank Wildensee (*City of Portland, Oregon*).

The project team would also like to extend sincere thanks to Troy Meyers, Ph.D. (*Luther College, Iowa*) and Susan Knapp (*Knapp Design, Minnesota*) for their assistance with the report.

Report Preparation

Principal Investigator:

Scott D. Wallace P.E.

North American Wetland Engineering LLC

Project Team:

Robert L. Knight, Ph.D.

Ronald A. Clarke, Jr., M.S.

Wetland Solutions, Inc.

Jaime A. Nivala, M.S.

Curtis J. Sparks P.E.

North American Wetland Engineering LLC

Gene F. Parkin, Ph.D., P.E.

The University of Iowa

Project Subcommittee

Ralph Beeman

DuPont

Donald S. Brown

U.S. Environmental Protection Agency

J. Steven Glass

The City of Albuquerque

Robert H. Kadlec, Ph.D., P.E.

Wetland Management Services Inc.

James F. Kreissl
Environmental Consultant

John T. Novak, Ph.D., P.E., Chair
Virginia Tech

Kevin D. White, Ph.D., P.E.
University of South Alabama

Water Environment Research Foundation Staff

Director of Research:	Daniel M. Woltering, Ph.D.
Program Director:	Amit Pramanik, Ph.D.
Program Manager:	Jennifer Simmons

ABSTRACT AND BENEFITS

Abstract:

The expanding use of decentralized wastewater management has resulted in an increased interest in small-scale wetland treatment systems. However, there is limited information available on the use, distribution of, and performance of these wastewater treatment systems. The purpose of this study was to address this knowledge gap by developing criteria for the feasibility, design, operation, and maintenance of small-scale wetland systems.

A total of 1640 small-scale treatment wetlands was identified as part of the data collection effort for this project. The data obtained came from a variety of wetlands with different design parameters, loading rates, and geographic locations. The data was used to develop sizing criteria for the two most common types of small-scale treatment wetlands: free water surface (FWS) wetlands and vegetated submerged bed (VSB) wetlands for removal of the following wastewater constituents: biochemical oxygen demand (BOD), total suspended solids (TSS), total Kjeldahl nitrogen (TKN), total phosphorus (TP).

In addition to the sizing criteria, this manual provides basic information on wastewater generation, the feasibility of wetland technology, and internal treatment processes in constructed wetlands. Important design issues such as hydraulic considerations, cold-climate performance, operations and maintenance, vegetation establishment, and construction costs are also presented in this report.

Benefits:

- ◆ Describes the feasibility of small-scale constructed wetland technology.
- ◆ Evaluates the use, distribution, and performance of small-scale constructed wetlands.
- ◆ Presents a comprehensive review of the state of understanding in wetland treatment processes, with detailed charts and illustrations of internal processes that will facilitate wetland design and operation.
- ◆ Presents design criteria based on the actual performance of existing small-scale wetland systems.
- ◆ Provides guidance for evaluating the conservativeness of a wetland design.
- ◆ Provides guidance for wetland plant selection and establishment.
- ◆ Describes key procedures for operation and maintenance of wetland treatment systems.

Keywords: treatment wetland, FWS wetland, VSB wetland, design, operation and maintenance, decentralized wastewater management

TABLE OF CONTENTS

Acknowledgments.....	iii
Abstract and Benefits.....	v
List of Tables.....	ix
List of Figures.....	xii
List of Acronyms.....	xvii
Executive Summary.....	ES-1
1.0 Introduction.....	1-1
1.1 Wastewater Management.....	1-2
1.2 Historical Use of Wetlands for Sewage Treatment.....	1-7
1.3 Types of Constructed Wetlands.....	1-9
1.4 Summary.....	1-13
2.0 Wastewater.....	2-1
2.1 Components of Sewage.....	2-2
2.2 Types of Collection Systems.....	2-5
2.3 Determination of Design Flows.....	2-5
2.4 Pathogens.....	2-12
2.5 Summary and Standardized Design Values.....	2-14
3.0 Use, Distribution, and Performance of Small-Scale Wetland Treatment Systems.....	3-1
3.1 Types of Wetland Treatment Systems at the Small-Scale Level.....	3-2
3.2 Application of Small-Scale Wetland Treatment Systems.....	3-2
3.3 Geographic Distribution of Small-Scale Treatment Wetlands.....	3-3
3.4 Distribution of Small-Scale Treatment Wetlands by Size and Flow.....	3-4
3.5 Biochemical Oxygen Demand (BOD) Performance.....	3-6
3.6 Total Suspended Solids (TSS) Performance.....	3-7
3.7 Total Kjeldahl Nitrogen (TKN) Performance.....	3-8
3.8 Total Phosphorus (TP) Performance.....	3-9
3.9 Summary.....	3-9
4.0 Wetland Treatment Processes.....	4-1
4.1 Water Balance.....	4-1
4.2 Frictional Losses.....	4-4
4.3 Dispersion and Short-Circuiting.....	4-10
4.4 Organic Matter Degradation.....	4-14
4.5 Suspended Solids Removal.....	4-19
4.6 Nitrogen Transformations.....	4-21
4.7 Phosphorus Cycling.....	4-27
4.8 Nutrient Uptake by Wetland Vegetation.....	4-29
4.9 Sulfur Cycling.....	4-30
4.10 Pathogen Reduction.....	4-30
4.11 Water Temperature.....	4-32
4.12 Summary.....	4-43

5.0	How Free Water Surface (FWS) Wetlands Work	5-1
5.1	Removal Mechanisms in FWS Wetlands	5-2
5.2	FWS Wetland Compartments	5-5
5.3	Role of Plants in FWS Wetlands	5-7
5.4	Oxygen Transfer in FWS Wetlands	5-10
5.5	Summary	5-12
6.0	Design of FWS Wetland Treatment Systems	6-1
6.1	Pretreatment	6-1
6.2	FWS Wetland Sizing for Pollutant Reduction	6-1
6.3	Hydraulic Design of FWS Wetlands	6-10
6.4	Internal Configuration of FWS Wetlands	6-13
6.5	Summary	6-18
7.0	How Vegetated Submerged Bed (VSB) Wetlands Work	7-1
7.1	History of VSB Technology Development	7-1
7.2	Removal Mechanisms in VSB Wetlands	7-10
7.3	VSB Wetland Compartments	7-12
7.4	Role of Plants in VSB Wetlands	7-14
7.5	Oxygen Transfer in VSB Wetlands	7-19
7.6	Summary	7-20
8.0	Design of VSB Wetland Treatment Systems	8-1
8.1	Pretreatment	8-1
8.2	VSB Wetland Sizing for Pollutant Reduction	8-2
8.3	Hydraulic Design of VSB Wetlands	8-12
8.4	Internal Configuration of VSB Wetlands	8-24
8.5	Summary	8-26
9.0	Wetland Plants	9-1
9.1	Wetland Plant Hydrology	9-2
9.2	Plant Selection for FWS Wetlands	9-5
9.3	Plant Selection for VSB Wetlands	9-12
9.4	Weeds	9-22
9.5	Wetland Planting Stock	9-22
9.6	Planting Wetland Vegetation	9-25
9.7	Successful Plant Establishment	9-26
9.8	Summary	9-28
10.0	Operation and Maintenance of Wetland Treatment Systems	10-1
10.1	Operation and Maintenance of FWS Wetlands	10-1
10.2	Operation and Maintenance of VSB Wetlands	10-8
10.3	Monitoring and Permit Compliance	10-14
10.4	Summary	10-17
11.0	Cost of Wetland Treatment Systems	11-1
11.1	Regional Markets and Economies of Scale	11-1

11.2	Basic Cost Components	11-2
11.3	Capital Costs	11-14
11.4	Operation and Maintenance Costs	11-17
11.5	Summary	11-19
12.0	Special Applications of Wetland Treatment Systems.....	12-1
12.1	Dairy and Milkhouse Wastewater.....	12-1
12.2	Landfill Leachate	12-4
12.3	Water Containing Petroleum Hydrocarbons.....	12-9
12.4	Pulp & Paper Wastewater	12-12
12.5	Acid Mine Drainage.....	12-14
12.6	Heavy Metals	12-16
12.7	Winery Wastewater.....	12-17
12.8	Summary	12-18
Appendix A: Modeling Wetland Effluent Concentrations		A-1
References.....		R-1

LIST OF TABLES

1-1	Wastewater Infrastructure Models	1-2
2-1	Typical Per-Person Waste Generation Rates	2-3
2-2	Typical Per-Person Combined Sewage Generation Rates	2-3
2-3	Per-Bedroom Prescriptive Flow Rates in Minnesota.....	2-7
2-4	Average Per-Person Wastewater Flows by Location.....	2-8
2-5	Types of Pathogens.....	2-13
2-6	Standardized Per-Person Wastewater Generation Rates.....	2-14
3-1	Small-Scale Wetland Treatment Systems by Type.....	3-2
3-2	Small-Scale Wetland Treatment Systems by Waste Type.....	3-2
3-3	Small-Scale Wetland Treatment Systems by Country.....	3-3
4-1	Evapotranspiration – Pan Evaporation Correlations in VSB Wetlands.....	4-2
4-2	Hydraulic Efficiency of VSB Wetland Cells at Tennessee Technological University	4-12
4-3	Hydraulic Efficiency of a VSB Wetland in Curienne, France.....	4-12
4-4	Removal Efficiencies for VSB Cells of Varying Depth.....	4-19
4-5	Solubility of Metal Hydroxides and Sulfides.....	4-30
4-6	Fecal Coliform Reduction for an Experimental FWS Wetland in Thailand.....	4-31
4-7	Thermal Conductivities of Common Wetland Materials.....	4-37
4-8	Ice Formation for FWS Wetland Example	4-39
5-1	Removal Mechanisms in FWS Wetlands	5-3
5-2	Background Concentrations for FWS Wetlands in This Study	5-10
6-1	Recommended FWS Wetland Areal Loading Rates.....	6-9
7-1	Summary of Media Used in VSB Wetland in the U.S. and Europe	7-10
7-2	Removal Mechanisms in VSB Wetlands.....	7-11
7-3	Background Concentrations for VSB Wetlands	7-17
7-4	Estimated CBOD ₅ Background Concentrations for Various As-Constructed VSB Mulch Materials	7-19
8-1	Recommended VSB Wetland Areal Loading Rates	8-8
8-2	Hydraulic Conductivity of “Clean” and “Dirty” VSB Wetland Bed Media.....	8-17
8-3	Recommended VSB Wetland Dimensioning Criteria	8-18

9-1	Plant Indicator Categories.....	9-3
9-2	Specific Surface Area for Various Treatment Systems	9-5
9-3	Species Suitable for Planting FWS Wetlands.....	9-6
9-4	Species Suitable for Planting VSB Wetlands	9-12
9-5	Invasive Plant Species in North American Constructed Wetlands.....	9-22
11-1	Earthwork Costs for Selected VSB Wetlands.....	11-4
11-2	Liner and Geotextile Costs for Selected VSB Wetlands	11-6
11-3	Granular Bedding Costs for Selected VSB Wetlands.....	11-7
11-4	Media Costs for Selected VSB Wetlands	11-8
11-5	Planting Costs for Selected VSB Wetlands	11-10
11-6	Distribution Costs for Selected VSB Wetlands Using 100-mm Perforated PVC Pipe.....	11-11
11-7	Distribution Costs for Selected VSB Wetlands Using Infiltration Chambers	11-11
11-8	Hydraulic Control Structure Costs for Selected VSB Wetlands.....	11-12
11-9	Miscellaneous Costs for Selected VSB Wetlands	11-13
11-10	Capital Costs for an FWS Wetland.....	11-14
11-11	Selected 2001 Bid Results for a VSB Wetland on the U.S.-Canadian Border	11-16
11-12	Example Operating Budget for a 46-Home Residential Development in Minnesota.....	11-18
12-1	WERF Small-Scale Wetland Treatment Systems by Waste Type.....	12-1
12-2	Pollutant Characteristics of Raw Cow Milk	12-2
12-3	University of Vermont Dairy Farm Waste Stream Characteristics	12-3
12-4	University of Connecticut Milkhouse Waste Stream Characteristics.....	12-3
12-5	Vertical-Flow Wetland Dimensioning Criteria for Milkhouse Waste.....	12-4
12-6	Typical Leachate Characteristics Over Time.....	12-5
12-7	Leachate Treatment Performance for an FWS Wetland near Pensacola, Florida.....	12-6
12-8	Landfill Leachate Nitrogen Reductions for FWS and VSB Wetlands in North Carolina	12-6
12-9	Nitrification of Landfill Leachate Using Aerated VSB Wetlands in Canada.....	12-7
12-10	Leachate Treatment Using Vertical Flow Wetlands in Italy	12-9
12-11	Petroleum Hydrocarbon Removal in a VSB Wetland	12-10

12-12 Areal Rate Coefficients (k_A , m/yr, based on 3 TIS) for Pilot-Scale VSB Wetland Cells Treating Petroleum Hydrocarbons in Casper, Wyoming	12-11
12-13 Mean Areal 3-TIS Rate Coefficients for Combination FWS + Aerated VSB Wetland System Treating Petroleum Hydrocarbons in Casper, Wyoming	12-11
12-14 Effect of Substrate Depth on Pollutant Removal in Vegetated VSB Wetlands Polishing Pretreated Pulp Mill Effluent at a 15-Hour Retention Time.....	12-13
12-15 Post-Facultative Pond Wastewater Characteristics of a Winery near Hopland, California.....	12-17
12-16 First-Order Decay Constant and Retardation Coefficients for Pollutant Removal from Hopland, California, VSB Wetlands During the Non-Crush Period	12-18
A-1 Statistical Analysis for Modeling the Wyoming Dataset with the Wyoming Model	A-2
A-2 Statistical Analysis for Modeling the Ham Lake Dataset with the Wyoming Model ...	A-2

LIST OF FIGURES

1-1	1927 Sears Roebuck Advertisement for a Septic Tank	1-3
1-2	Infiltration Rate for Restaurant Effluent (A), Septic Tank Effluent (B), Graywater (C), Tap Water (D).....	1-4
1-3	Theoretical Approach to Decentralized Wastewater Management	1-6
1-4	1901 U.S. Patent for a Constructed Wetland System	1-8
1-5	Constructed Wetland Technology Envelope	1-9
1-6	FWS Wetland Schematic	1-10
1-7	Typical Application of an FWS Wetland.....	1-11
1-8	Typical Application of a VSB Wetland.....	1-11
1-9	VSB Wetland Schematic.....	1-12
2-1	Use of Treatment Wetland with Graywater/Blackwater Separation.....	2-4
2-2	Feasibility of Treatment Wetland Technology	2-6
2-3	Idealized Water Use Pattern for an Individual Home.....	2-9
2-4	Effect of Collection System Size on Wastewater Flow Variation.....	2-9
2-5	Effect of Pumping on Flow Delivery.....	2-10
3-1	Distribution of Design Flow for Small-Scale FWS and VSB Wetlands	3-4
3-2	Distribution of Footprint Area for Small-Scale FWS and VSB Wetlands	3-5
3-3	Distribution of BOD Concentrations for Small-Scale Wetlands	3-6
3-4	Distribution of TSS Concentrations for Small-Scale Wetlands.....	3-7
3-5	Distribution of TKN Concentrations for Small-Scale Wetlands	3-8
3-6	Distribution of TP Concentrations for Small-Scale Wetlands.....	3-9
4-1	Constructed Wetland Water Budget	4-1
4-2	Flow Schematic for an FWS Wetland	4-4
4-3	Flow Schematic for a VSB Wetland.....	4-5
4-4	Relationship Between Hydraulic Conductivity and Biomat Formation	4-6
4-5	Water Surface Profile of a Single-Home VSB Wetland in Alabama	4-6
4-6	Effect of Media Size and Biomat Formation on Hydraulic Conductivity	4-7
4-7	Biofilm Penetration Distance as a Function of Media Size	4-7
4-8	Stages of Clogging in VSB Wetlands.....	4-9
4-9	Comparison of Ideal Reactor Types	4-10

4-10	Tanks-In-Series (TIS) Model.....	4-11
4-11	Spatial Distribution of Tracer During a VSB Wetland Tracer Study	4-12
4-12	Difference in Transit Times for a VSB Wetland in Victoria, Australia	4-13
4-13	Classification of Organic Matter by Degradability.....	4-15
4-14	Weathering of Organic Matter During Wetland Treatment.....	4-16
4-15	Carbon Cycling in FWS Wetlands.....	4-18
4-16	Nitrogen Cycling in FWS Wetlands	4-24
4-17	Variability of TKN Removal in FWS Wetlands.....	4-25
4-18	Phosphorus Cycling in FWS Wetlands.....	4-28
4-19	Energy Transfers in Wetland Systems.....	4-32
4-20	Typical Balance Point Temperature Response for a Treatment Wetland.....	4-33
4-21	FWS Wetlands in Semi-Tropical and Cold Temperate Climates	4-34
4-22	FWS Wetland During Initial Ice Formation	4-36
4-23	FWS Wetland Under Normal Winter Operating Conditions.....	4-39
4-24	Energy Balance for a VSB Wetland (Simplified Winter Condition).....	4-41
4-25	Thermal Response of a Mulch-Insulated VSB Wetland in Minnesota.....	4-42
4-26	Annual Course of Air and Water Temperature for Two VSB Wetlands.....	4-42
5-1	Redox Conditions in an FWS Wetland.....	5-1
5-2	FWS Wetland near Pensacola, Florida	5-2
5-3	Major Ecological Processes in FWS Wetlands.....	5-5
5-4	Plant Adaptations to Wastewater Stresses in FWS Wetlands.....	5-8
5-5	Dissolved Oxygen (DO) Profile for a Facultative Lagoon	5-11
6-1	Example Loading Chart.....	6-3
6-2	FWS Areal Loading Chart for Biochemical Oxygen Demand.....	6-4
6-3	FWS Areal Loading Chart for Total Suspended Solids.....	6-5
6-4	FWS Areal Loading Chart for Total Kjeldahl Nitrogen	6-6
6-5	FWS Areal Loading Chart for Total Phosphorus	6-7
6-6	Fecal Coliform Reduction in Small-Scale FWS Wetlands.....	6-8
6-7	Recommended Water Depth for FWS Wetlands.....	6-10
6-8	FWS Wetland Cell Configuration for Design Example	6-13

6-9	Typical Outlet Control Structure for an FWS Wetland	6-14
6-10	Effect of Precipitation on Design Freeboard Capacity	6-16
6-11	Typical Deep Zone in an FWS Wetland	6-16
6-12	Seaming of Polyethylene Liner to Polyethylene Pipe.....	6-18
7-1	VSΒ Wetland for a Single-Family Home near Comfort Lake, Minnesota.....	7-1
7-2	Max Planck Institute Process Wetland Treatment System (Plan View).....	7-2
7-3	Max Planck Institute Process Wetland Treatment System (Profile View).....	7-3
7-4	Root Zone Method Treatment Wetland	7-3
7-5	Redox Conditions in the Rhizosphere.....	7-4
7-6	VSΒ Wetland in Germerswang, Germany	7-5
7-7	Single-Home Wastewater Treatment System Using Plants.....	7-7
7-8	VSΒ Wetland Schematic from TVA Wetland Design Manual	7-8
7-9	Hydraulic Conductivity Zones Within VSΒ Wetlands.....	7-9
7-10	Major Ecological Processes in VSΒ Wetlands	7-12
7-11	Internal Gas Spaces (Aerenchyma) within a <i>Phragmites australis</i> Root	7-14
7-12	Oxygen Transfer by <i>Phragmites australis</i>	7-15
7-13	Plant Adaptations to Wastewater Stresses in VSΒ Wetlands	7-16
7-14	VSΒ Wetland Thatch Accumulation in Los Ranchos, New Mexico.....	7-17
7-15	Impact of Mulch on CBOD ₅ Removal for Six Insulated VSΒ Wetlands in Minnesota.....	7-18
7-16	Oxygen Utilization in a VSΒ Wetland Sized Large Enough for Nitrification to Occur	7-20
8-1	VSΒ Areal Loading Chart for Biochemical Oxygen Demand.....	8-3
8-2	VSΒ Areal Loading Chart for Total Suspended Solids	8-4
8-3	VSΒ Areal Loading Chart for Total Kjeldahl Nitrogen.....	8-5
8-4	VSΒ Areal Loading Chart for Total Phosphorus.....	8-6
8-5	Fecal Coliform Reduction in Small-Scale VSΒ Wetlands	8-7
8-6	Extent of Ponding for Nine VSΒ Wetlands in Minnesota	8-13
8-7	Potential Pitfalls for Steeply Sloped VSΒ Wetland Designs.....	8-14
8-8	Flat-Bed VSΒ Wetland Design.....	8-15
8-9	Layout for a Basic VSΒ Wetland.....	8-18

8-10	Layout and Design Factors for a Constrained-Width VSB Wetland.....	8-19
8-11	Layout for VSB Wetland Hydraulics Design Example	8-20
8-12	VSB Wetland With Elevated Inlet Distribution Zone	8-22
8-13	VSB Wetland Outlet Control Structure	8-24
8-14	Rotating Standpipe for VSB Wetland Outlet Control Structure.....	8-25
8-15	VSB Wetland with Vertical Sidewall Under Construction in Casper, Wyoming	8-26
9-1	Hydrology of Plant Indicator Categories	9-3
9-2	Duck Potato (<i>Sagittaria latifolia</i>)	9-7
9-3	Softstem Bulrush (<i>Schoenoplectus validus</i>).....	9-8
9-4	Hardstem Bulrush (<i>Schoenoplectus acutus</i>)	9-9
9-5	Cattail (Broadleaf) (<i>Typha latifolia</i>).....	9-10
9-6	Cattail (Narrowleaf) (<i>Typha angustifolia</i>)	9-11
9-7	Swamp Milkweed (<i>Asclepias incarnata</i>).....	9-13
9-8	Canna Lily (<i>Canna spp.</i>).....	9-14
9-9	Taro (Elephant Ear) (<i>Colocasia esculenta</i>).....	9-15
9-10	Blueflag Iris (<i>Iris versicolor</i>).....	9-16
9-11	Umbrella Palm (<i>Cyperus alternifolius</i>).....	9-17
9-12	Reed Canarygrass (<i>Phalaris arundinacea</i>).....	9-18
9-13	Common Reed (<i>Phragmites australis</i>)	9-19
9-14	Green Bulrush (<i>Schoenoplectus atrovirens</i>).....	9-20
9-15	River Bulrush (<i>Schoenoplectus fluviatilis</i>)	9-21
9-16	Example of Healthy Plant Stock and Root Development.....	9-24
9-17	Potted-Plant Installation Procedure for a Standard FWS Wetland	9-25
9-18	Rhizome Planting Procedure for a Standard VSB Wetland.....	9-25
9-19	Potted-Plant Installation Procedure for a Mulch-Insulated VSB Wetland	9-26
9-20	Newly Planted FWS Wetland in Casper, Wyoming.....	9-27
9-21	Newly Planted (<i>a</i>) and Established (<i>b</i>) Mulch-Insulated VSB Wetland in Anamosa, Iowa	9-27
10-1	Recommended Operational Checks for FWS Wetland Outlet Control Structure.....	10-2
10-2	Typical Deep Zone in an FWS Wetland.....	10-5
10-3	Outlet Control Structure for a VSB Wetland.....	10-8

10-4	Water Level Settings During Plant Establishment in a VSB Wetland	10-9
10-5	Sub-Irrigation of Mulch Layer During Plant Establishment Phase in a Mulch-Insulated VSB Wetland.....	10-9
10-6	“Clean Bed” and “Clogged Bed” Water Level Response in VSB Wetlands.....	10-11
10-7	Inlet Header Modifications to Reduce Cross-Sectional Organic Loading in VSB Wetlands.....	10-12
10-8	Replacement of VSB Wetland Influent Distribution Header in Lake Elmo, Minnesota	10-13
10-9	Firebreak Between Cells of a VSB Wetland in Albuquerque, New Mexico.....	10-14
11-1	VSB Wetland Costs as Influenced by Regional Market and Size of Wetland System	11-2
12-1	Typical Application of a Constructed Wetland for Treatment of Dairy Waste	12-2
12-2	Typical Application of a Constructed Wetland for Treatment of Landfill Leachate	12-5
12-3	Nitrogen Concentrations in a VSB Wetland Treating Landfill Leachate	12-8
12-4	VSB Wetland Aeration System Before <i>(a)</i> and After Replacement <i>(b)</i>	12-8
12-5	Petroleum Hydrocarbon Wetland Treatment System in Casper, Wyoming	12-12
12-6	Typical Application of a Constructed Wetland for Treatment of AMD	12-15
12-7	Iron Removal as a Function of Effluent pH.....	12-15
12-8	Manganese Removal as a Function of Effluent pH	12-16
12-9	Typical Application of a VSB Wetland for Treatment of Winery Wastewater.....	12-17
A-1	Modeling Results for Two VSB Wetlands (Biochemical Oxygen Demand)	A-1
A-2	Areal Loading Chart for Biochemical Oxygen Demand	A-4
A-3	FWS Areal Loading Chart for Total Suspended Solids.....	A-4
A-4	FWS Areal Loading Chart for Total Kjeldahl Nitrogen	A-5
A-5	FWS Areal Loading Chart for Total Phosphorus.....	A-5
A-6	VSB Areal Loading Chart for Biochemical Oxygen Demand.....	A-6
A-7	VSB Areal Loading Chart for Total Suspended Solids	A-6
A-8	VSB Areal Loading Chart for Total Kjeldahl Nitrogen.....	A-7
A-9	VSB Areal Loading Chart for Total Phosphorus	A-7

LIST OF ACRONYMS

AMD	Acid Mine Drainage
BOD	Biochemical Oxygen Demand
BOD ₅	5-day Biochemical Oxygen Demand
BOD _u	Ultimate Biochemical Oxygen Demand
BTEX	Benzene-Toluene-Ethylbenzene-Xylene
Bti	<i>Bacillus thuringiensis</i> variety <i>israelensis</i>
CBOD ₅	Carbonaceous 5-day Biochemical Oxygen Demand
CEC	Cation Exchange Capacity
CFU	Colony Forming Unit
COD	Chemical Oxygen Demand
CSTR	Continuously Stirred Tank Reactor
DO	Dissolved Oxygen
DOC	Dissolved Oxygen Carbon
EC/EWPCA	European Community/European Water Pollution Control Association
ENR CCI	Engineering News Record Construction Cost Index
EP	Pan Evaporation
ET	Evapotranspiration
FAC	Facultative
FACU	Facultative Upland
FACW	Facultative Wetland
FC	Fecal Coliform
FISH	Fluorescent In-Situ Hybridization
FWS	Free Water Surface
GFA	Gesellschaft zur Förderung der Abwassertechnik
GPD	gallons per day
GRO	Gasoline Range Organics
Ha	hectare
HDPE	High Density Polyethylene
HRT	Hydraulic Retention Time
IWA	International Water Association
LECA	Light Expanded Clay Aggregate
LLDPE	Linear Low-Density Polyethylene
L:H	Length-to-Height
L:W	Length-to-Width
MPIP	Max Planck Institute Process
MTBE	Methyl <i>tert</i> -Butyl Ether
NABD	North American Treatment Wetland Database
NASA	National Aeronautics and Space Administration
OBL	Obligate
ÖNORM	Österreichisches Normungsinstitut
O&M	Operation and Maintenance
PE	Population Equivalent
PFR	Plug Flow Reactor
PVC	Polyvinyl Chloride
SAV	Submerged Aquatic Vegetation
TIS	Tanks-in-Series

TKN	Total Kjeldahl Nitrogen
TN	Total Nitrogen
TPH	Total Petroleum Hydrocarbons
TP	Total Phosphorus
TSS	Total Suspended Solids
TVA	Tennessee Valley Authority
U.K.	United Kingdom
UPL	Upland
U.S.	United States
USD	United States Dollars
USPHS	United States Public Health Service
UV	Ultraviolet
VF	Vertical Flow
VIP	Ventilated Improved Pit
VSF	Vegetated Submerged Bed
WERF	Water Environment Research Foundation

EXECUTIVE SUMMARY

The use of constructed wetlands for treatment of domestic wastewater has increased exponentially in the past decade, especially for small-scale applications such as individual homes and small communities. Despite the abundant use of wetland technology at this scale, the majority of small wetland systems are permitted at the local level and fall below state or provincial permitting thresholds, making them difficult to locate. Moreover, performance monitoring and reporting requirements for small-scale systems varies widely by geographic location. As a result, there is no central source of information on small-scale wetland systems. Small-scale wetland designs are often based on best professional judgment or borrowed design equations from other treatment technologies, such as facultative lagoons.

The purpose of this study was to provide guidance for the designers and operators of such small-scale wetland systems. This report discusses the feasibility of constructed wetland technology (Chapter 1.0); identifies wetland technologies that are appropriate for small-scale treatment systems (Chapter 2.0); evaluates the use, distribution, and performance of small-scale wetlands identified in this study (Chapter 3.0); reviews the state of understanding in wetland treatment processes (Chapter 4.0); provides information on removal mechanisms and design guidance particular to free water surface (FWS) wetlands (Chapters 5.0 and 7.0) and vegetated submerged bed (VSB) wetlands (Chapters 6.0 and 8.0); presents information on wetland plant selection and establishment (Chapter 9.0), operations and maintenance (Chapter 10.0), cost (Chapter 11.0); and ends with a discussion on special applications of wetland technology (Chapter 12.0).

The data collection effort of this study resulted in the identification of 1,640 wetland systems meeting the size (6 ha) and flow ($2,000 \text{ m}^3/\text{d}$) threshold to be considered small-scale. Of the wetlands identified in this study, only 6% overlap with those reported in the North American Treatment Wetland Database (U.S. EPA, 1997b). Approximately 23% of the 1,640 systems reported treat wastewater from individual homes ($2.6 \text{ m}^3/\text{d}$ or less), and 89% of the systems reported serve populations of 5,000 people or fewer ($1000 \text{ m}^3/\text{d}$). The vast majority of wetland systems reported (93%) were VSB wetlands. Because VSB wetlands do not have an open water surface, exposure to pathogens is minimized. This attribute encourages preferential use of this technology for individual homes and small communities.

This report also provides guidance on the two most crucial aspects of small-scale wetland design: hydraulics and pollutant removal. Hydraulic considerations for VSB wetlands are discussed in detail. Areal loading charts for pollutant removal in FWS and VSB wetlands were developed for common wastewater constituents (biochemical oxygen demand, total suspended solids, total Kjeldahl nitrogen, and total phosphorus) based on first-order pollutant removal rates and non-zero background concentrations.

CHAPTER 1.0

INTRODUCTION

How do small-scale wastewater projects differ from large ones?

In private practice, engineers quickly realize that small-project design can be much more challenging than large-project design. Issues that arise during the large-project design process (technology selection, site planning, specifications, cost estimates, etc.) also arise in the design of small projects. Addressing all of these design issues in small projects can be difficult because they often have limited resources and budgets.

Small wastewater projects also differ from large projects in regards to operations and maintenance. Unlike larger, more conventional systems, small projects cannot afford the services of a full-time, dedicated operations and maintenance (O&M) staff. Most small-scale systems rely on periodic visits by a system operator; often funding allows an operator to visit a site just once or twice a month. Even then, the operator budget may limit system visits to a few hours at a time. Small treatment systems are held to the same effluent standards as large treatment works, and must be simple and robust in order to operate continually with minimal attention. Given this situation, the appropriate technology for small-scale treatment works must:

- ◆ Produce a consistent effluent quality despite variable flow and loading.
- ◆ Operate without constant tweaking and adjustment.
- ◆ Minimize the use of mechanical equipment because equipment can break often or malfunction between operator visits).
- ◆ Be constructed out of local materials (especially in developing countries).

Due to these factors, there is an increasing interest in the use of constructed wetlands in the field of decentralized wastewater management (U.S. EPA, 1997a). Wetlands are simple treatment systems that mainly rely on passive treatment processes. From a public perspective, they are an environmentally responsible treatment process.

Although wetland technology has been studied since 1952 (Seidel, 1973) and has been in full-scale operation since 1974 (Kickuth, 1977), our understanding of wetland treatment processes is still evolving. New applications of wetland technology are still being developed.

The current state-of-the-art design approaches can be characterized as *semi-empirical* (partly quantitative and partly empirical). For large wetland treatment systems, designers typically use a quantitative method to determine the overall size of a system (Kadlec and Knight, 1996; U.S. EPA, 2000a). However, current designers of small-scale systems lack the quantitative design information that is available for larger systems. Small-scale wetland treatment systems are often sized on best judgment or by using equations borrowed from other treatment technologies, such as facultative lagoons.

The goal of this manual is to provide effective tools for the design, operation, and maintenance of small-scale wetland treatment systems. Due to the unique factors that must be considered in decentralized wastewater management, engineers need simple, yet robust tools for designing wetland treatment systems.

1.1 Wastewater Management

The concept of decentralized wastewater management arises from a realization that conventional, large-scale treatment works cannot cost-effectively solve the wastewater management problems in areas of low population density and/or low capital investment (U.S. EPA, 1997a). There are three basic models of wastewater infrastructure (Hallahan and Wallace, 2001), as shown in Table 1-1.

Table 1-1. Wastewater Infrastructure Models.
Adapted from Hallahan and Wallace, 2001.

Population Density	Infrastructure Type
High	Regional sewer networks (the “Big Pipe”)
Medium	Cluster systems
Low	Single-home systems (onsite septic systems)

1.1.1 Regional Sewer Networks (“The Big Pipe”)

Building sewers to transport waste away from urban areas is an ancient practice. The practice of building sewers in urban areas dates back to 7,000 BC (Bertrand-Krajewski, 2003). The great sewer of Rome, the Cloaca Maxima, was built around 550–500 BC (Smith, 1875). In many large urban areas, wastes were often deposited into cesspools and vaults. This material was often removed by scavengers or farmers and applied to nearby farm fields. In the mid 1800s, eight U.S. cities (including New York, Baltimore, Cleveland, and Washington, D.C.) sold their night soil to processors who made it into fertilizer (Del Porto and Steinfeld, 2000). As water distribution systems were installed in urban areas, the use of flush toilets gained popularity and dramatically increased the volume of wastewater discharged to the cesspools. This resulted in overflows and increased maintenance costs, and citizens soon began to demand better sanitary conditions. This led to the development of regional sewer networks capable of carrying the sewage away from the population centers.

In developed countries, the conventional engineering focus has been to design wastewater infrastructure based on the regional (Big Pipe) model. This model is generally characterized by gravity sewers, activated sludge or trickling filter treatment, and surface water outfalls. In the United States, the Clean Water Act of 1972 provided funding to construct wastewater treatment plants under the regional infrastructure model. The objective was to provide secondary (biological) treatment of wastewater. Between 1972 and 1996, the number of people in the United States served by secondary or advanced wastewater treatment systems increased from 85

to 173 million (Fox, 1999). Since grant and loan dollars were allocated based on need, and need was determined in part by the number of people served, the majority of financial assistance went to large metropolitan areas.

Cost estimates to continue building regional infrastructure capable of addressing the wastewater needs in the United States range between \$200 and \$330 billion U.S. dollars (USD) (Fox, 1999). Between 1972 and 1996, the United States invested approximately \$70 billion USD in wastewater infrastructure (Fox, 1999). The funding required to continue building wastewater infrastructure under this paradigm is economically infeasible. To address this problem, other infrastructure models such as cluster and single-home systems must be considered.

1.1.2 Single-Home Systems (Onsite Septic Systems)

In areas without running water, sewage was often managed by separating it from population centers. For instance, the first sanitation law in Virginia (Virginia Department of Health, 1610), read, in part:

“...nor shall anyone aforesaid, within a quarter of one mile from the Pallizadoes, dare to doe the necessities of nature, since by these unmanly, slothful, and loathsome immodesties, the whole fort may bee choked and poisoned with ill aires, and so corrupt (as in all reason cannot but much infect the same) and this shall they take notice of and avoide, upon paine of whipping and further punishment, as shall thought meete, by the censure of a martiall court...”

As flush toilets gained in popularity, the volume of sewage requiring disposal dramatically increased. During this time the relationship between sanitation and disease also became more widely accepted, and there was a push towards a more hygienic means of sewage disposal: keep it underground. Underground disposal of sewage evolved into leach fields, a practice in which septic tank effluent is dispersed over a large area of land. Since leach pits quickly clog with raw sewage, a settling device (septic tank) was developed (Figure 1-1).

Hercules Septic Tank for Sewage Disposal

Instructions furnished with each tank.

Hercules Septic Tank Where First Stage of Purification Takes Place

The filter or absorption bed where liquid effluent from tank passes through the final purifying stage before soaking into the soil.

Typhoid and other disease germs, in almost every instance, can be traced to contamination of the well by house sewage. A safe and efficient system of sewage disposal is recognized as a necessity for the protection of human life. Hercules Septic Tank is adapted for sewage disposal from any building where running water is available. The natural process of bacterial action provides a safe, effectual and inexpensive means of sewage disposal, as well as an effective protection for your water supply. Hercules tanks are built from high quality Copper Bearing Steel Plate, unexcelled for rust resistance. In addition to this, they are coated with a special rust resisting preservative, making them very durable.

It Kills the Germs

Removable Metal Top

METAL BAFFLE PLATES

SLUDGE CHAMBER EFFLUENT CHAMBER

Bacteria Acting on Sewage

Catalog No.	Diameter, inches	Height, inches	Total Cap. Gals.	Shipping Weight	Capacity Home Use, Persons	Price
42K3562/5	30 1/4	48	153	165	4	\$20.65
42K3563/5	36	48	212	205	6	\$22.40
42K3564/5	45	48	331	300	8	\$28.00

Above prices do not include drain tile.
Shipped from factory in WESTERN NEW YORK or NORTHERN ILLINOIS whichever is nearer you.

Figure 1-1. 1927 Sears Roebuck Advertisement for a Septic Tank. Reprinted with permission from Alan Mirken (editor), 1970, Crown Publishers Inc. Library of Congress card no. 78-108061.

The septic tank was developed in France in the 1860s (Kriessl, 2002), and a two-compartment septic tank was patented in the United States in 1881 by Edward Philbrick (United States Public Health Service, 1949). Once established in the United States, the septic tank and size of the soil absorption system were codified through prescriptive design standards at the local level. In many jurisdictions, prescriptive septic codes are still used as a de-facto land management tool in lieu of zoning.

Direct application of sewage to a soil adsorption system results in the accumulation of biomass in the pore space of the soil, and is commonly referred to as a biomat. The biomat reduces the ability of the soil to accept wastewater (U.S. EPA, 1980). As organic matter is continually applied, the soil particles eventually clog, leading to hydraulic failure of the adsorption system (Tyler and Converse, 1994). Figure 1-2 illustrates the effect of waste strength on subsurface infiltration rate. Waste streams with high loadings of organic matter, such as commercial and domestic wastes, will exhaust a soil absorption system much faster than lightly loaded waste streams, such as those receiving graywater. Tap water, which contains virtually no organic matter, can be applied to a soil absorption system ad infinitum. Well-managed onsite systems can last 20 years or more, although the average lifespan is much shorter (7–10 years) due to lack of proper operation and maintenance.




Figure 1-2. Infiltration Rate for Restaurant Effluent (A), Septic Tank Effluent (B), Graywater (C), and Tap Water (D). Reprinted with permission from Tyler and Converse, 1994, American Society of Agricultural Engineers.

In the United States during the early 1900s, adequate backup areas could easily be identified for soil adsorption systems in rural areas of low population density. The growth of the suburbs after World War II began to challenge the assumption that there would always be ample space available for back-up soil adsorption systems; land availability soon became limited. Continuing to use an onsite treatment system coupled with a soil adsorption system was considered an acceptable practice as long as they were perceived as a temporary measure (e.g., until the regional sewer network arrived).

With the recognition that even wealthy countries such as the United States cannot afford to replace all onsite systems with regional sewer networks, there is renewed interest in pretreatment technologies that can extend the effective life of onsite treatment systems by reducing biomat formation and subsequent failure of soil adsorption systems.

1.1.3 Cluster Systems

Cluster systems serve a small group of residences. While there are no absolute limits on what constitutes a cluster system, these systems typically serve communities ranging from two to 200 homes. Cluster systems differ from regional sewer networks in that cluster infrastructure provides a collection, treatment, and disposal system for each population node, whereas the regional sewer network attempts to tie all population nodes to a single large treatment works. Cluster systems borrow technology from both the onsite and regional sewer industries. Due to their small size, alternative collection systems such as pressure sewer or small diameter gravity sewer are often used in conjunction with septic tanks (U.S. EPA, 1991). These systems are also more likely to use subsurface dispersal (similar to that of an onsite system) rather than surface water discharge, which is utilized by regional treatment works.

The increasing interest in cluster systems closely tracks the increasing interest in decentralized wastewater management. Cluster systems avoid the high collection costs of regional sewer networks and result in far fewer treatment systems than the single-home approach. Having fewer systems simplifies operation and maintenance, while having multiple users for each system creates the financial wherewithal to adequately fund operation and maintenance.

In developed countries, cluster systems can provide cost-effective sewage treatment for small villages and towns. In the United Kingdom, Severn Trent Water was faced with the need to upgrade treatment works in the early 1990s. Severn Trent had over 1,000 sewage treatment works, 732 of which served populations of less than 2,000. These small works, while representing over 70% of the systems, served less than 3% of Severn Trent's customer base (Green and Upton, 1994). Cluster systems could be a cost-effective solution in Austria, where an estimated 15% of the population (1.2 million people) are living in communities of less than 500 people and still lack wastewater treatment (Haberl et al., 1998). Cluster systems are also becoming popular in new residential developments in the United States.

1.1.4 Wastewater Management in Developing Countries

The "Big Pipe" wastewater infrastructure of developed countries does not necessarily provide a road map for cost-effective infrastructure elsewhere in the world. Even in North America and Western Europe, sewage treatment needs still are not being effectively addressed for small communities.

The world population has increased from approximately 2.5 billion people in 1950 to 6.3 billion people in 2003 (United Nations, 2003). Approximately 81% of the world population lives in developing countries (Population Reference Bureau, 2002). As the world population has grown, it has shifted from rural to urban areas. The world's urban population was 2.3 billion in 1990 and is projected to be 4.6 billion in 2020, with 93% of this growth occurring in less developed countries (Mara, 1996b).

The shift from rural to urban areas has created dense population centers that lack basic sanitation facilities. The number of people without adequate sanitation is estimated to be 2.4 billion (Postel, 2003); approximately 38% of the world population. Dense population centers without basic sanitation create conditions ripe for disease. Lack of clean water or sanitation kills an estimated 3.3 million people each year, most of which are children (Postel, 2003). Approximately 40% of the world's population (in over 80 countries and regions) are experiencing water stress (Glieck, 1993), forcing exploitation of water reserves. This short-term

strategy is likely to have detrimental long-term effects on the availability of fresh water for human communities and native ecosystems (Kivaisi, 2001). A theoretical framework for sustainable wastewater management has been developed for Zimbabwe (Nhapi et al., 2003), but is applicable to many other regions throughout the globe (see Figure 1-3).




Figure 1-3. Theoretical Approach to Decentralized Wastewater Management.
Reprinted with permission from Nhapi et al., 2003, IWA Publishing.

This model illustrates that for low-density areas, wastewater is best managed at the individual property level, using single-home (onsite) systems with household recycling of effluent water. As housing density increases, the optimum sewage infrastructure cascades into a cluster system approach. At this medium density level, preferred technologies are land-based (simple and low cost) since residents cannot afford full-time operators. Reuse of the effluent for irrigation or other uses is preferred. As housing density approaches urban levels, insufficient space is available for land-based treatment systems and the preferred sewage infrastructure cascades again, this time to a regional sewer network with full-time treatment plant operators.

1.1.5 Role of Constructed Wetlands in Decentralized Wastewater Management

Wetland treatment systems use a simple technology that fits very well into both the single-home (onsite) management and medium-density cluster system approach. Specific situations that are good candidates for wetland treatment include:

- ◆ Small rural communities where waste stabilization ponds cannot be employed.
- ◆ Residential clusters in areas where regional infrastructure is not available or cannot be provided cost-effectively.

- ◆ Small businesses, resorts, campgrounds, schools and restaurants that cannot be served by regional infrastructure.
- ◆ Individual homes in areas where conventional onsite septic systems have high failure rates, cannot be replaced (due to inadequate backup area), or are not appropriate (due to high groundwater levels).

Constructed wetlands are attached-growth biological filters that distinguish themselves from more conventional treatment processes because they utilize vegetation that is adapted to grow in saturated (or nearly saturated) environments. With the inclusion of vegetation, treatment wetlands have the appearance of a natural wetland habitat and employ many of the biological processes found in natural wetland ecosystems.

Currently there are estimated to be over 50,000 wetland treatment systems worldwide (Kadlec, 2004), with interest in wetland treatment spreading rapidly. Using plants to purify wastewater has tremendous appeal to the general public. Within the regulatory and design community, interest has been sustained because of the simplicity of treatment wetlands. Wetland systems are one of the few technologies that can produce a biologically treated effluent (to secondary or better standards) with a sufficiently low pathogen content. Wetland systems can achieve this level of treatment with minimal external mechanical or energy input and operator support. Because these systems can be constructed from local materials and are simple to operate and maintain, they have the potential for widespread applications in developing countries. Constructed wetlands are currently in use in a variety of countries, including Tanzania, South Africa, Peru, Colombia, Mexico, Egypt, Turkey, Nepal, Thailand, India, and China.

1.2 Historical Use of Wetlands for Sewage Treatment

The sewage farming experiences of the 1870s in the United Kingdom led to an appreciation of the link between wastewater application rates, wetland hydrology, plant adaptation, and wastewater purification. It was noted in 1877 that the application of $6 \text{ m}^3/\text{m}^2\text{-day}$ ($147 \text{ gal}/\text{ft}^2\text{-day}$) of sewage quickly produced a foul-smelling swamp with a polluted effluent; reduction of wastewater applications to $0.05 \text{ m}^3/\text{m}^2$ ($1.2 \text{ gal}/\text{ft}^2\text{-day}$) with underdrains allowed the sewage farms to operate without soil clogging (Cooper and Boon, 1987). This led to a standardization of wastewater loadings at about 0.25 m^2 per person per day (2.7 ft^2 per person per day) (Hiley, 1994), which was sufficient to maintain wastewater application areas as grass plots.

By 1900, the idea of creating wetlands specifically for wastewater treatment had been developed. An essay to the Hornsby Literary Institute, NSW, Australia in 1904 states in part (Brix, 1994b):

“...The drainage of suburban houses is always giving trouble and is a matter about which people seem utterly helpless. In districts where there is no sewerage system, householders find that every day they have a large amount of dirty water to dispose of, and the difficulty is to know how to get rid of it. People who live on high ground throw it into an open drain and let it run away to the lower ground where it generates foul gases which breed disease. Others allow all their dirty water to run into the street where it flows along the gutters filling the air with foul odors and causing typhoid and kindred maladies...”

If every householder disposed of his own drainage on his own premises as he might very well do, the health of all of us would be much improved. Anyone who has a little ground about his house can dispose of his dirty water as follows:

Dig up a plot of ground thoroughly to a depth of fifteen to eighteen inches. Cut a channel leading from the kitchen and washhouse into the highest side of the plot and let all the dirty water drain into it. Plant the plot with plants that grow rapidly and require a great deal of water such as Arum Lilies, for instance. The dirty water will be all absorbed by the roots of the plants and a most luxuriant garden will be produced which will defy the hottest weather and will always be green and beautiful. By this means a curse will be transformed into a blessing."

The first documented use of a wetland within a deliberately engineered treatment vessel appears to belong to Cleophas Monjeau (Monjeau, 1901), as shown in Figure 1-4.




Figure 1-4. 1901 U.S. Patent for a Constructed Wetland System.

Claims for this U.S. patent (issued in 1901) include distributed vertical flow, a fluctuating water level, and aeration of the wastewater. This would be considered a cutting-edge wetland design even in the 21st century.

1.3 Types of Constructed Wetlands

Little knowledge from the initial wetland technology of the late 19th century was carried over to the engineered wetlands developed in the late 20th century. Modern constructed wetlands are man-made systems that have been designed to emphasize specific characteristics of the wetland habitat for improved treatment capacity. Treatment wetlands can be constructed in a variety of hydrologic types. The overall technology envelope for constructed wetland systems is summarized in Figure 1-5.




Figure 1-5. Constructed Wetland Technology Envelope.

Four types of constructed wetlands have been found in widespread use for small-scale wastewater treatment applications:

- ◆ Free water surface (FWS) wetlands have areas of open water and are similar in appearance to natural marshes.
- ◆ Vegetated submerged bed (VSB) wetlands employ a soil or gravel bed planted with wetland vegetation. The water, kept below the surface of the gravel, flows horizontally from the inlet to the outlet.
- ◆ Vertical flow (VF) wetlands distribute water across the surface of a sand or gravel bed planted with wetland vegetation. The water is treated as it percolates down and through the plant root zone.
- ◆ Sludge dewatering beds (reed beds) use the evapotranspiration capacity of emergent wetland plants (typically *Phragmites*) to dewater sewage sludge.

1.3.1 Free Water Surface (FWS) Wetlands

These wetlands contain areas of open water, floating vegetation, and emergent plants. Depending upon local regulations and soil conditions, berms, dikes, and liners can be used to control flow and infiltration. As the wastewater flows through the wetland, it is treated by the processes of sedimentation, filtration, oxidation, reduction, adsorption, and precipitation (U.S. EPA, 2000a). The components in a typical FWS wetland are shown in Figure 1-6.




Figure 1-6. FWS Wetland Schematic.

Since FWS-constructed wetlands closely resemble natural wetlands, it should be no surprise that they attract a wide variety of wildlife, namely insects, mollusks, fish, amphibians, reptiles, birds, and mammals (Knight et al., 1993; Kadlec and Knight, 1996). Because of the